

## High resolution terajets using 3D cuboids

Pacheco-Peña, V.; Beruete, M.; Navarro-Cia, Miguel; Minin, I. V.; Minin, O. V.

DOI:

[10.1109/USNC-URSI.2015.7303484](https://doi.org/10.1109/USNC-URSI.2015.7303484)

License:

None: All rights reserved

*Document Version*

Peer reviewed version

*Citation for published version (Harvard):*

Pacheco-Peña, V, Beruete, M, Navarro-Cia, M, Minin, IV & Minin, OV 2015, High resolution terajets using 3D cuboids. in *Radio Science Meeting (Joint with AP-S Symposium), 2015 USNC-URSI*. Institute of Electrical and Electronics Engineers (IEEE), pp. 200. <https://doi.org/10.1109/USNC-URSI.2015.7303484>

[Link to publication on Research at Birmingham portal](#)

### General rights

Unless a licence is specified above, all rights (including copyright and moral rights) in this document are retained by the authors and/or the copyright holders. The express permission of the copyright holder must be obtained for any use of this material other than for purposes permitted by law.

- Users may freely distribute the URL that is used to identify this publication.
- Users may download and/or print one copy of the publication from the University of Birmingham research portal for the purpose of private study or non-commercial research.
- User may use extracts from the document in line with the concept of 'fair dealing' under the Copyright, Designs and Patents Act 1988 (?)
- Users may not further distribute the material nor use it for the purposes of commercial gain.

Where a licence is displayed above, please note the terms and conditions of the licence govern your use of this document.

When citing, please reference the published version.

### Take down policy

While the University of Birmingham exercises care and attention in making items available there are rare occasions when an item has been uploaded in error or has been deemed to be commercially or otherwise sensitive.

If you believe that this is the case for this document, please contact [UBIRA@lists.bham.ac.uk](mailto:UBIRA@lists.bham.ac.uk) providing details and we will remove access to the work immediately and investigate.

## High Resolution Terajets Using 3D Dielectric Cuboids

Víctor Pacheco-Peña<sup>(1)</sup>, Miguel Beruete<sup>(1)</sup>, Miguel Navarro-Cía\*<sup>(2,3)</sup>, Igor V. Minin<sup>(4)</sup>, and Oleg V. Minin<sup>(4)</sup>

(1) Universidad Pública de Navarra, Pamplona 31006, Spain,  
miguel.beruete@unavarra.es

(2) Imperial College London, London SW7 2AZ, UK, m.navarro@imperial.ac.uk

(3) University College London, London WC1E 7JE, UK

(4) Siberian State Academy of Geodesy, Plahotnogo 10, Novosibirsk, 630108,  
Russia, prof.minin@gmail.com

The limit imposed intrinsically by the diffraction of electromagnetic waves has been extensively studied with the aim to improve the performance of microscopy techniques and to obtain subwavelength resolution. Several techniques have been proposed to solve this disadvantage such as metamaterials and microspherical particles, to name a few.

With the aim to obtain subwavelength focusing, we report here an alternative mechanism to produce jets at Terahertz frequencies (terajets) by using 3D dielectric cuboids illuminated with a planewave with the electric field along  $y$   $E_y$  (V. Pacheco-Peña et al., Applied Physics Letters, 105, 084102, 2014). Similarly to the recently proposed micro scaled cylindrical (2D) and spherical (3D) dielectrics at optical frequencies, the dielectric cuboids demonstrate that a focus with subwavelength resolution can be obtained just at the output surface of the cuboid. The dielectric cuboid has lateral dimensions  $L = \lambda_0$  along  $x$  and  $y$  axes while the dimension along  $z$  is  $H = 1.2\lambda_0$ . The performance of the terajet produced by this structure is evaluated numerically by changing its refractive index from 1.2 up to 2 when it is immersed in vacuum ( $n_0 = 1$ ) demonstrating a quasi-spherical terajet just at the output surface of the cuboid when its refractive index is 1.41. Moreover, a full comparison between the 3D dielectric cuboid and its 2D counterpart is performed using a metal particle inserted within the terajet region and evaluating the backscattering enhancement. Demonstrating that both structures are able to produce 3D (spherical) and 2D (teraknife) jets and to enhance the backscattering of particles placed within this region.

The performance of the terajets produced by the dielectric cuboids are evaluated numerically and experimentally at sub-THz frequencies, using a cuboid made of Teflon ( $n = 1.46$ ) with air as background. Experimental and simulation results of the power distribution along the transversal  $x$  axis are carried out at the distance  $z = 0.1\lambda_0$  demonstrating a good agreement between them with a focusing enhancement (ratio of the power distribution received at the focal position evaluated with and without the 3D dielectric cuboid) of  $\sim 10$  times the incident plane wave.